

Total Recall VR LinX Omnia is a professional, hybrid and standalone voice logging and call recording system with very high analogue, IP and digital (ISDN) recording channel density suitable for hybrid analogue, VoIP, RoIP, RTP, AoIP and ISDN audio logging and call recording applications.

This model is capable of recording:

- Calls on analogue telephone lines via a high impedance (Hi-Z) analogue line tap.
- Audio from any line level analogue audio source.
- SIP sessions (calls) via SPAN port.
- SIP sessions (calls) via UDP/TCP port.
- SIPrec sessions via UDP/TCP port.
- Cisco BiB sessions via TCP/UDP port.
- H.323 calls via SPAN port.
- Unicast and multicast RTP streams via SPAN port.
- Unicast and multicast RTP streams via a UDP port.
- RTSP sessions via UDP/TCP port.
- ATC recording via ED-137.
- RoIP (analogue, MPT-IP and DMR networks) recording via Tait VRP.
- RoIP (DMR networks) recording via Hytera HDAP.
- RoIP (analogue, DMR, P25, NXDN ... networks) recording via Omnitronics RTP.
- RoIP (analogue, DMR, P25, NXDN ... networks) recording via Zetron SIP logging interface.
- ISDN (Q.931) calls on ISDN PRI links via high impedance (Hi-Z) link tap.

The maximum recording channel capacity of this model is:

- 60 analogue recording channels; or
- 60 IP recording channels; or
- 60 ISDN recording channels; or
- 60 IP and ISDN recording channels in any combination; or
- 60 analogue plus 60 IP and ISDN recording channels in any combination.

Compliance: 

Built specifically for the purpose of hybrid audio logging and call recording and running on a Linux platform that utilises hot-swap RAID storage technology, it is highly reliable and tolerant to system and storage faults. It uses a redundant hot-swappable power supply for 24/7 uninterrupted operation. It is a professional hybrid call recording solution with no compromise on features and affordable price.

Key features:

- Convenient 19" rack mountable enclosure.
- Intel and Linux based platform for outstanding reliability and performance.
- Built in control panel featuring a colour LCD display and easy access keys.
- Ideal for hybrid analogue source (telephone, microphone, audio output ...), VoIP and ISDN PRI call recording.
- Fault resilient audio storage.
- Fault resilient power supply.
- Tamper proof audio media and file format.
- Multi-level user access control.
- User-configurable voice logging and call recording with functions like start/stop recording and record-on-demand.
- Non-intrusive, live and real-time monitoring of recordings in progress.
- Playback of completed recordings while recording in progress.
- Start, stop, pause, fast-forward and fast-reverse player controls.
- Comprehensive search options including time, date, call numbers, extension, agent name, key words in notes and much more.
- On-board audio storage and archive up to 380,000 hours of audio at 8Kbps and/or 60,000 hours at 64Kbps.
- On-demand and automatic archiving at predefined intervals to CD, DVD or Blu-Ray media.
- Network archiving to archive unlimited number of recordings to a network drive.
- USB key and disk drive archiving.
- SNMP alarm integration.
- Station Messaging Detail Record (SMDR) integration for many popular PaBX systems.
- 3 Activation Licenses for any of the following PC applications with every system: [Total Recall VR Desktop](#), [Total Recall VR Manager](#), [Total Recall VR Monitor](#), [Total Recall VR Browser](#), [Total Recall VR Event Player](#) and [Total Recall VR Audio Player](#).
- 2 years warranty (that can be extended to 3, 4 or 5 years).

Options:

- Solid state hard drive (SSD) to improve performance and reliability.
- AMBE decoder license.
- Double audio storage.



Distributed in North America by:
OMNICRON ELECTRONICS
www.omnicronelectronics.com